

26 - 06 - 2006 1810661 DMKI-FPTER0

designation	Impresario Chronis RTS Lounge
reference	1810661
range	RTS New Collection

FUNCTIONS

Hand held transmitter to create and play scenarios + Incorporated timer function.
Automatic mode when transmitter hold on its wall support / Manual mode when out of the support.

- Up to 16 scenarios / 6 days / 3 weeks.
- Up to 20 addresses
- Sun management function



- Local control mandatory
- Compatibles with the RTS receivers range except for access applications

Available languages: GB D NL I E P F Installation guide language in : D NL I F

TECHNICAL SPECIFICATIONS

Box	Material Color Size Protection factor against solid & splashproof	ABS and SEBS Grey & Silver 174 x 56 x 26 mm IP 30
Battery	Voltage Type	4.5V 3 x AAA
Battery life time (at ambient temperature)		2 years (4 actions of 1" per day)
Frequency Radiated power Modulation type Protocole		433.42 Mhz +/- 100 kHz 0dBm or 1 mW ASK type A1 RTS
Standard		EN 60730 - 2 - 1 EN 300220 - 3 EN 301489 - 3
Temperature range	Storage Working	- 20°C / + 70°C 0°C / + 60°C
Antenna		Integral
Drop test		1.5 m
Wear resistivity		250 cycles of abrasion with a jeans.
Cleaning products resistivity		products for glass (with alcohol) for various use, javel water (dilution 1/5)
Weight		approx. 165g

R&D Name: X. COLET	QUALITY Name: L. GUILLOT	EDITOR Name: BROZILLE. F
Date: 24/07/06	Date: 5/02/06	Date: 29-06-2006